

# **Toolbox for 3D Planning and Risk Assessment of Ammunition Field Depots**

F.K.F. Radtke, I. Stacke, M. Voss, C. Rizzuti, I. Häring

Fraunhofer-Institute for High-Speed Dynamics – Ernst-Mach-Institute,  
Am Klingenberg 1, 79588 Efringen-Kirchen, Germany  
radtke@emi.fhg.de, haering@emi.fhg.de

## **Keywords:**

planning of ammunition field storage, risk assessment of field camps, explosive ordnance disposal, EOD, risk management, hazard analysis, damage analysis, explosive safety, industrial foundation classes, IFC, forward operating base, rocket, artillery mortar (RAM) threat

## **Abstract**

A growing number of international missions of the German armed forces leads to an increasing need for ammunition storage in field depots. Therefore improved planning and risk assessment tools are needed. Type and intensity of an international mission determine the number of deployed troops and the terrain available for field camps. This defines also type and amount of required ammunition as well as storage conditions. From limitations of space and available personnel the need of optimized planning arises, including the comparison of different solutions for field depots. During the deployment changes of the mission may occur. The presented 3D planning tool for ammunition field depots allows easy and fast adaptation of the existing storage layout to changed situations. The tool is based on military regulations. It makes intense use of databases, computational geometry and relational algebra. Some risks caused by the stored ammunition and given limitations cannot be avoided. We show how the German explosive safety quantitative risk analysis software (ESQRA-GE) is applied to representative planning scenarios. The ESQRA-GE follows an established risk assessment methodology. Based on the modelling of physical hazards and damage, individual and collective risks are computed. Past experience has shown that, in addition to interior threats caused by stored ammunition, shelling poses a major threat. The level of passive protection against rockets provided by representative structures of the field depot for the ammunition is evaluated employing the code "risk analysis software for forward operating bases – rocket, artillery, mortar (RAFOB-RAM)". The presented 3D tools allow the planning of ammunition field depots following the current technical guidelines of the NATO and the German Armed Forces. They provide functionalities to assess the risk due to stored ammunition and threats resulting from rocket shelling.

Report Documentation Page		Form Approved OMB No. 0704-0188
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.		
1. REPORT DATE <b>JUL 2010</b>	2. REPORT TYPE <b>N/A</b>	3. DATES COVERED <b>-</b>
4. TITLE AND SUBTITLE <b>Toolbox for 3D Planning and Risk Assessment of Ammunition Field Depots</b>		5a. CONTRACT NUMBER
		5b. GRANT NUMBER
		5c. PROGRAM ELEMENT NUMBER
6. AUTHOR(S)	5d. PROJECT NUMBER	
	5e. TASK NUMBER	
	5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) <b>Fraunhofer-Institute for High-Speed Dynamics Ernst-Mach-Institute, Am Klingenberg 1, 79588 Efringen-Kirchen, Germany</b>		8. PERFORMING ORGANIZATION REPORT NUMBER
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)		10. SPONSOR/MONITOR'S ACRONYM(S)
		11. SPONSOR/MONITOR'S REPORT NUMBER(S)
12. DISTRIBUTION/AVAILABILITY STATEMENT <b>Approved for public release, distribution unlimited</b>		
13. SUPPLEMENTARY NOTES <b>See also ADM002313. Department of Defense Explosives Safety Board Seminar (34th) held in Portland, Oregon on 13-15 July 2010, The original document contains color images.</b>		
14. ABSTRACT <b>A growing number of international missions of the German armed forces leads to an increasing need for ammunition storage in field depots. Therefore improved planning and risk assessment tools are needed. Type and intensity of an international mission determine the number of deployed troops and the terrain available for field camps. This defines also type and amount of required ammunition as well as storage conditions. From limitations of space and available personnel the need of optimized planning arises, including the comparison of different solutions for field depots. During the deployment changes of the mission may occur. The presented 3D planning tool for ammunition field depots allows easy and fast adaptation of the existing storage layout to changed situations. The tool is based on military regulations. It makes intense use of databases, computational geometry and relational algebra. Some risks caused by the stored ammunition and given limitations cannot be avoided. We show how the German explosive safety quantitative risk analysis software (ESQRA-GE) is applied to representative planning scenarios. The ESQRA-GE follows an established risk assessment methodology. Based on the modelling of physical hazards and damage, individual and collective risks are computed. Past experience has shown that, in addition to interior threats caused by stored ammunition, shelling poses a major threat. The level of passive protection against rockets provided by representative structures of the field depot for the ammunition is evaluated employing the code risk analysis software for forward operating bases rocket, artillery, mortar (RAFOB-RAM). The presented 3D tools allow the planning of ammunition field depots following the current technical guidelines of the NATO and the German Armed Forces. They provide functionalities to assess the risk due to stored ammunition and threats resulting from rocket shelling.</b>		
15. SUBJECT TERMS		

16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT <b>SAR</b>	18. NUMBER OF PAGES <b>34</b>	19a. NAME OF RESPONSIBLE PERSON
a. REPORT <b>unclassified</b>	b. ABSTRACT <b>unclassified</b>	c. THIS PAGE <b>unclassified</b>			

## **Brief presenter biography**

Frank Radtke started his working career as a research associate at TU Delft after finishing his studies of civil engineering at the University of Hannover with a Dipl.-Ing.. Since 2009 he has been working at the Fraunhofer-Institute for High-Speed-Dynamics, Ernst-Mach-Institute in the hazard and risk analysis group. His work was mainly focused on ammunition storage safety and counter terrorism.

## **1 Introduction**

In this concept paper we present an integrated approach for planning and assessment of field camps with a main focus on ammunition storage safety and passive structural protection against RAM-threats (overhead and side protection).

Since a couple of years NATO nations face an increasing number of deployed missions. Compared to the cold war era the type of conflict has changed. Instead of one symmetric high intensity conflict a number of smaller asymmetric conflicts with changing intensities occurs. This means that at the beginning of a mission the intensity might be low and thus only a small number of light-armed forces is needed. But when the intensity grows the capabilities have to be adapted which means that more forces with different equipment are sent to theatre. But this also means that a field camp that has been planned for e.g. light infantry might need to accommodate armoured troops as well as artillery. Regarding ammunition storage different amounts and types of ammunition need to be taken into account.

Resources for planning, construction, protection and operation of field camps and field depots are always scarce. To increase complexity a field camp might be operated by different nations potentially having different regulations regarding e.g. safety issues.

Naturally, the main threat originates from a possibly hostile environment. This might be for example rocket, artillery or mortar shelling (RAM-threat). Also in this case, the scenario is constantly changing.

To respond to this situation we are developing a toolbox of different interconnected software tools to support planning and operating field camps with the focus on ammunition field depots and protective structures against RAM-threats.

The first step is the partially automated site planning of ammunition field depots following standard guidelines. If it is not possible to comply with appropriate regulations, a more detailed analysis of the field depot is performed using a risk model. Regarding exterior threats a model is employed describing the risk due to rocket, artillery and mortar (RAM) shelling.

## 2 Automated Site Planning of Ammunition Field Storage

### 2.1 Objective

The automated site planning tool is supposed to be mainly used during the planning of an ammunition field depot. But it should also support changes becoming necessary during the use of the facility.


The user should be able to specify local boundary conditions as e.g. geographical conditions and choose from standard configurations which can be adapted to special needs.

As a result the user gets fully usable site plans including the needed resources as for example number and type of ISO containers, geometry and material data, or the amount of concrete for storage buildings.

In addition, it should be possible to enter the military forces and automatically compute their required ammunition.

### 2.2 Approach

In a first step the deployed military forces are specified which includes the specification of the intensity of the conflict, the number of soldiers and the duration of the deployment. Based on this information and based on regulations and experience of the German Armed Forces the program calculates the required amount and type of ammunition (as an example of the program output refer to Figure 1).




Ammunition_ID	Weapon_System_ID1	Ammunition_Name	Ammunition_Set	Ammunition_Exchange_Code
1	1	5,56x45 mm	25	AA59
2	1	5,56x45 mm	25	AA63
3	2	7,62x47 mm	25	AA31
4	2	7,62x47 mm	25	AA33
5	3	9x19 mm	12	AA80
6	4	9x19 mm	6,4	AA80
7	5	7,62x51 mm	120	AA24
8	6	Munition FFP 93	6,3	AA71
9	7	Munition Leuchtspur	3	CA04
10	8	Munition M82A1	6,37	AA14
11	9	40x45 mm	24	BB20
12	9	40x45 mm	24	BB22
13	9	40x45 mm	24	BB28
14	10	40x45 mm	24	BB31
15	11	Handgranate	2	CA70
16	12	20x139 mm	120	AT53
17	12	20x139 mm	120	AT78
18	13	20x139 mm	120	AT53
19	13	20x139 mm	120	AT74
20	14	35x228 mm	200	BB24
21	14	35x228 mm	200	BB27
22	15	120x50 mm	7	CB01
23	15	120x50 mm	7	CB12
24	16	120 mm	45	CA00
25	16	120 mm	45	CA06
26	16	120 mm	45	CA07
27	16	120 mm	45	CA04
28	17	ChaffFlare	40	CA00
29	17	ChaffFlare	120	AA10
30	18	155 mm SMART	76	OP20

Figure 1: Example of the output of required ammunition generated by the ammunition field depot planning tool.

Based on this information, including the organizational structure of the deployed forces and taking into account the appropriate regulations as e.g. [1, 2] a field depot is generated as qualitatively depicted in Figure 2. Constraints due to the geometry of the storage structure and the packaging of the ammunition are considered as well as typical numbers of ammunition stored within a package.

The software automatically checks if the layout of the field depot complies with the regulations, e.g. safety distances (QDs). In addition, it ensures that the appropriate type

of storage structure is used for the stored ammunition. If this is not possible within the given boundary conditions, hazard, damage and risk analysis can be conducted.



Picture Source: WTD-52

Figure 2: Example of an ammunition field depot; each military unit gets a storage assignment within the storage area of the national forces e.g. the German forces; each storage assignment may consist of different types of storage structures.

### 3 Risk Assessment of Internal Threads due to Ammunition Storage

If it is not possible to follow the regulations when planning an ammunition field depot, it might become necessary to perform a hazard, damage and risk analysis. Based on this analysis the depot might be optimized to reach an acceptable level of safety.

#### 3.1 Objective

The German explosive safety quantitative risk analysis model (ESQRA-GE) is intended for the assessment of non-standard situations in ammunition storage, where existing guidelines cannot be applied.

#### 3.2 Approach

In Figure 3 the risk management scheme for explosive events employed at EMI is depicted. The first step is the scenario definition. In the presented integrated approach the scenario definition is performed using the ammunition depot planning tool output as described in Section 2. In the future we will directly import this data into the risk analyses software ESQRA-GE.

For a defined scenario the physical hazards as fragment throw or blast can be calculated as shown in Figure 4.

Based on the physical hazards, consequences, e.g. damage of buildings or the number of injured persons, can be computed.

Including the fractional exposure of persons to hazards, and the frequency of an event e.g. an unwanted explosion, the individual risk of persons can be evaluated. In this way a scenario can be adapted such that safety is guaranteed to an acceptable level even if it is not possible to comply with standard guidelines.




Figure 3: Risk management methodology employed at Fraunhofer Ernst-Mach-Institute (EMI).

The ESQRA-GE is described in more detail in [3–5].




Figure 4: Density of all fragments (left) and density of fragments fulfilling the NATO criterion (right); fragment shadows due to barriers around the storage containers are clearly visible.

## 4 Risk Assessment of External Threats due to Shelling

So far, we have considered hazards originating from inside a field camp as possible threats. But naturally we also have to take into account a possibly hostile environment. Current missions have shown that a major threat consists of the shelling of field camps with rockets, artillery and mortar shells. Therefore, we develop a risk analysis (RA) tool for forward operating bases (FOB) analyzing the effect of passive protection against RAM. The tool RAFOB-RAM is supposed to use the output of the ammunition depot planning tool as scenario input for a part of the analysed field camp.

### 4.1 Objective

The aim of the risk analysis model for forward operating bases (RAFOB-RAM) is to assess different types of risk for personnel due to rockets, artillery or mortar shells fired into a field camp as depicted in Figure 5.

Mitigation effects due to passive protection are taken into account. The aim is to detect weak points of the passive protective measures – in particular in the ammunition storage facilities.

For instance, for certain ammunition classes – high energy fragments cause initiation of ammunition. Thus, ammunition storage sites might become hazards sources. Even more, if sympathetic detonation must be considered.






Figure 5: Example scenario with depiction of the outdoor exposure volume elements possibly containing persons.

## 4.2 Approach

First, possible trajectories of RAM ammunition are calculated leading to a number of representative impact trajectories in the camp as shown in Figure 6.

We consider different types of fuses and impact scenarios. Depending on the fuse type we calculate for each representative impact trajectory the effects of representative initiations in air, at impact or after perforation of structures. The fragment trajectories are calculated. If the shell hits a building, penetration or perforation of the building are computed. This generates threats inside a building due to primary fragments and secondary debris from the building itself.

Knowing the fragment trajectories and specifying areas where people are located possible injuries with different levels of severity can be calculated. To assess injuries for persons we use a three dimensional representation of a human being taking into account individual protection levels and positions (voxel model) [6].

Finally, using event frequency and fractional exposure of persons to different threats, local and global individual and collective risks can be computed.

This information can be applied to identify critical components of the building structures and to minimize resulting risks by employing structural hardening or protective measures, e.g. barriers.

Figure 6 shows two calculated scenarios, where 625 representative initiation points were calculated for the warhead of an unguided 107 mm rocket fired from 4 km away. The upper part of the figure shows an atrium building with massive outer walls and a thick concrete roof. In the lower part the same building is protected on three sides with 2 m high walls. The protective barriers lead to a significant reduction of the injury probability inside the building, as illustrated in the picture. Apparently the applied protective measure is appropriate for a more effective passive protection. All possible single events

for a rocket with an impact fuse were considered, i.e. the consideration of more representative impact trajectories leads to the same results close to the building.




Figure 6: Minimization of consequences inside an atrium building with protective barriers.

## 5 Industry Foundation Classes as Interface Between Different Models

For users it is of highest importance to connect the different models in an efficient way. Thus an interface for stable data exchange has to be defined. For this purpose we have decided to use the Industry Foundation Classes (IFC) as data exchange format defined in an ISO standard [7]. This ISO-standard is currently introduced to a number of CAD tools. It has the advantage of storing all necessary data including geometrical data and material data in an efficient hierarchical layer like structure as shown in Figure 7. An example might be an ammunition storage house, where in addition to geometrical data material data such as Young's modulus or fracture energy can be assigned to the different objects in the file-format. This will enable us, for example, to compute within models like ESQRA-GE (refer to Section 3) and RAFOB-RAM (refer to Section 4) penetration or perforation of barriers and walls by fragments in an efficient way. At the same time the format contains all the information needed in the planning tool (refer to Section 2) to generate site plans and resource lists.

An important aspect regarding usability of the presented tools is the realistic visualization (refer to Figure 8) of scenarios, and analysis of results using the IFC format.




Figure 7: Layer structure of the industrial foundation classes (IFC) [8].




Figure 8: Visualization of a typical building; screenshot taken from IFC Viewer, Forschungszentrum Karlsruhe [9].

## 6 Conclusions

We have presented the concept of a framework for the planning of ammunition storage field depots, the risk assessment of ammunition storage depots in or close to field camps and the assessment of RAM-threats for field camps including ammunition storage depots. This framework enables us to assess interior and exterior threats, and allows to respond dynamically to changing needs of the German Armed Forces during their out-of-area missions.

## 7 Acknowledgements

The cooperation with the German armed forces and the Technical Centre of the German Armed Forces WTD 52 and especially with Mr. Steyerer and Mr. Dirlewanger is gratefully acknowledged. The work of Mr. Dörr and Mr. Gürke on the ESQRA-GE is gratefully acknowledged as well. Furthermore, we would like to thank our students K. Willuweit and C. Zühlsdorf for their contributions.

## References

1. Wehrtechnische Dienststelle 52: Leitfaden Baulicher Schutz bei Bevorratung von Munition im Einsatz (2007)
2. Streitkräfteunterstützungskommando: Weisung Munitionstechnische Sicherheit bei der Bevorratung von Munition im Einsatz (MunTSichhBevMunE) (2008)
3. Doerr, A., Guerke, G., Ruebarsch, D.: The German risk-based explosive safety code. In: 30th DoD Explosives Seminar (2002)
4. Doerr, A., Gürke, G., Ruebarsch, D.: The German explosive safety code ESQRA-GE. In: US DoD (ed.) 32nd Dod Explosive Saftey Seminar 2006 (2006)
5. Dörr, A., Voss, M., Gürke, G.: Technisches Handbuch ESQRA-GE Version 2.0 (2007)
6. Voss, M., Dörr, A., Rizzuti, C., Häring, I.: Risk analysis for forward operating bases, rocket, artillery, Mortar (RAFOB-RAM), Abschlussbericht 2009 (2010)
7. International Organization for Standardization (ISO): Inustry Foundation Classes, Release 2x, Specification (IFC2x Platform) (2005)
8. Liebiech, T., Jeffrey, W.: IFC Technical Guide. Industry Foundation Classes - Release 2x
9. IfcViewer, Karlsruhe Institute of Technology, Institut für Angewandte Informatik

---

# TOOLBOX FOR 3D PLANNING AND RISK ASSESSMENT OF AMMUNITION FIELD DEPOTS

---


F.K.F. Radtke, I. Stacke, M. Voss,  
C. Rizzuti, I. Häring

Corresponding author: Radtke, [radtke@emi.fhg.de](mailto:radtke@emi.fhg.de)  
Häring, [haering@emi.fhg.de](mailto:haering@emi.fhg.de)

# Outline


- Introduction
- Site planning tool
- Risk assessment for ammunition field depots and field camps regarding internal threats
- Risk assessment for ammunition field depots and field camps regarding external threats
- Interface between the different tools
- Conclusions

# Framework for Planning and Assessment of Field Camps and Ammunition Field Depots






# Site Planning Tool




Picture Source: WTD-52

# Program Flow



## Data Structure of the Site Planning Tool



# Digitization of Regulations

## Example: Compatibility Groups

416. Munition darf gemäß nachfolgender Tabelle zusammengelagert werden:

	B	C	D	E	F	G	H	J	L	S
B	X	O	O	O	O	O				X
C	O	X	X	X	O	X <sub>1</sub>				X
D	O	X	X	X	O	X <sub>1</sub>				X
E	O	X	X	X	O	X <sub>1</sub>				X
F	O	O	O	O	X	O				X
G	O	X <sub>1</sub>	X <sub>1</sub>	X <sub>1</sub>	O	X				X
H							X			X
J								X		X
L									L	
S	X	X	X	X	X	X	X	X		X

X Zusammenlagerung zulässig  
O Trennwand erforderlich  
X<sub>1</sub> Trennwand erforderlich für Munition des Gefahrkodes 1.1G  
L Zusammenlagerung nur zulässig, wenn die Gegenstände den gleichen gefährlichen Stoff enthalten.

SQLite Administrator - AmmunitionToolDatabase.s3db

Datenbank Tabelle Index View Trigger Abfrage Daten Hilfe

AMMUNITIONTOOLDATABASE

- Tabellen
  - Ammunition
  - AmmunitionCompatibility
  - AmmunitionStorage
  - AmmunitionStorageFieldDistance
  - MaximumExplosiveQuantity
  - WeaponSystem
- Indizes
- Views
- Trigger
- Abfragen


SQL Abfrage Ergebnis Datensätze editieren

Tabelle: AmmunitionCompatibility


Filterfeld: Filter:

Ammunition	Compatibility_ID	Compatibility_Group_1	Compatibility_Group_2	Permission
1	B	B	X	
2	B	C	O	
3	B	D	O	
4	B	E	O	
5	B	F	O	
6	B	G	O	
7	B	H	-	
8	B	J	-	
9	B	L	-	
10	B	S	X	
11	C	C	X	
12	C	D	X	
13	C	E	X	
14	C	F	O	
15	C	G	X <sub>1</sub>	
16	C	H	-	
17	C	J	-	
18	C	L	-	
19	C	S	X	
20	D	D	X	


# Internal and External Threats



# Risk assessment for Ammunition Field Depots




# Internal Threats – ESQRA-GE



# ESQRA-GE: Assessment of an Ammunition Field Depot Regarding Internal Threats


Ammunition Field Depot






# ESQRA-GE: Assessment of an Ammunition Field Depot Regarding Internal Threats

All Fragment Density




# ESQRA-GE: Assessment of an Ammunition Field Depot Regarding Internal Threats

NATO Fragment Density




# ESQRA-GE: Assessment of an Ammunition Field Depot Regarding Internal Threats





Damage Zone for Vehicles:  
Zone C – slight or no damage




# External Threats – ESQRA-GE




# RAFOB-RAM: Assessment of an Ammunition Field Depot Regarding External Threats



# RAFOB-RAM: Assessment of an Ammunition Field Depot Regarding External Threats




# RAFOB-RAM: Assessment of an Ammunition Field Depot Regarding External Threats





# RAFOB-RAM: Assessment of an Ammunition Field Depot Regarding External Threats






# IFC – Format: Interface Between the Different Tools



Quelle: [www.koramic.de](http://www.koramic.de)




Quelle: Google SketchUp


3D CAD-Data, Material Data, Strength of Material, Amount of Reinforcement, Use

3D Vizualisation using IFC

# Structure of IFC Data Format



# IFC – Format: Interface between the Different Tools



Screenshot taken from IFC Viewer, Forschungszentrum Karlsruhe

# Conclusions

